

Technische Angaben Axial-Rührwerk ODERMATT

odermatt 
RÜHREN&PUMPEN

Art.Nr.	Typ	KW	Nenn- strom	Propeller-ø	Scheidwand- Ausparung	H-Drehzahl	Decken-Ausparung auf Boden montiert	Decken-Ausparung auf Säule montiert	Schaufeln Grösse
02.060.055	UT650-AX	5.5	8.6	2.80m	3.00m	16.75	ø250mm	ø200mm	700x500
02.060.075	UT650-AX	7.5	14.8	2.80m	3.00m	18.55	ø250mm	ø200mm	700x500
02.060.100	UT650-AX	9.3	20	2.80m	3.00m	20.58	ø250mm	ø200mm	700x500
							ø250mm	ø200mm	
02.060.110	UT800-AX	11	21	2.80m	3.00m	21.69	ø300mm	ø200mm	700x500
02.060.112	UT800-AX	11	21	3.30m	3.60m	17.88	ø300mm	ø200mm	700x500
02.060.116	UT800-AX	11	21	3.60m	4.00m	14,80	ø300mm	ø200mm	700x500
02.060.130	UT800-AX	11	21	4.20m	4.50m	14,00	ø300mm	ø250mm	700x500
02.060.155	UT900-AX	15	27.8	3.60m	4.00m	16.64	ø350mm	ø250mm	700x500
02.060.160	UT900-AX	15	27.8	4.20m	4.50m	14.94	ø350mm	ø250mm	700x500
02.060.185	UT950-AX	18.5	32.8	4.20m	4.50m	16,00	ø350mm	ø250mm	700x500